

# CONE BOTTOM TANKS

Snyder's mix tanks are available in sizes from 17 gallons to 110 gallons, while our cone bottom storage tanks hold from 475 gallons to 11,850 gallons. The 15°, 30° and 45° cone options provide fast discharge and complete drainage, and both our mix tanks and storage tanks feature engineered welded steel stands. Optional fitting locations and gallonage tapes are also available.

## CONE BOTTOM TANKS

Gallons	Diameter	Height w/stand	Manway	Part No.	Outlet Specs	Stand Required	FOB
<b>30° Cone Bottom</b>							
70	32"	50"	8"	H15601--	T		C
475	60"	69"	18"	H15603--	O	78801000	C
1000	86"	83"	10"	189--	O	79100000	L,C
1250	95"	84"	18"	8310--	O	90401202	M
1400	86"	93"	10"	190--	O	79100000	L,C
1600	95"	87"	18"	8330--	O	90401202	M
1775	86"	111"	10"	191--	O	79100000	L,C
2000	90"	125"	18"	5070--	O	79100000	L
2500	90"	148"	18"	5110--	O	79100000	L,C
2600	95"	125"	18"	8350--	O	90401201/1202	M
3000	90"	167"	18"	5150--	O	79100000	L,C
3000	95"	141"	18"	8360--	O	90401201/1202	M
5500	90"	255"	18"	7040--	O	79100000	L
6500	90"	296"	18"	7180--	O	79300000	L
6900	142"	160"	18"	5280--	O	79500000	L
8250	142"	184"	18"	5320--	O	79500000	L
11850	142"	239"	18"	5340--	O	79500000	L
<b>45° Cone Bottom</b>							
500	64"	81"	18"	6190--	O	78800000	L
1000	64"	120"	18"	5000--	O	78800000	L
1500	64"	158"	18"	5010--	O	78800000	L
2850	90"	163"	18"	5100--	O	79200000	L
4350	90"	217"	18"	5180--	O	79200000	L
<b>15° Cone Bottom</b>							
3000	90"	136"	18"	7460--	O	N/A	L



### OUTLET LEGEND:

Q = 10" or 18" fill, and one 2" bolted outlet.  
O = 18" manway, one 3" total drain bolted outlet.

Add 26" to the tank height to get overall height in stand.

## MIX TANKS

Gallons	Diameter	Height	Part No.	Outlet Specs	Stand Required	FOB
17	18 1/2"	34"	185--	K	48400000	L
35	31"	34"	158--	M	48600000	L
65	31"	41"	156--	M	48600000	L
110	31"	56"	607--	M	48600000	L



### OUTLET LEGEND

K = 8" screw-on cap, 1 1/4" outlet with anti-vortex.

L = Removable top, one 3/4" outlet, one 1 1/2" or 2 1/2" molded-in hose barb (optional 3/4" to 1 1/4" fitting available).

M = 10" fill, one 3/4" outlet, one 1 1/2" or 2 1/2" molded-in hose barb (1 1/4" fitting available).

### FEATURES:

- Molded-in gallonage markers (indicators).
- Slope bottom for easy draining and accurate measuring.
- Standard 1 1/4" fitting.
- UV inhibitors are molded in for longer tank life.

[www.snydernet.com](http://www.snydernet.com)



# CONE BOTTOM TANKS w/POLY STANDS

## STEEL CONE BOTTOM STANDS

CONE BOTTOM STANDS 30°	
Part No.	Description
79000000	86" 1000-1450-1650 Cone Stand (4 leg)
79100000	90" 45 ton gross weight capacity Cone Stand (8 leg)
79300000	90" 45 ton gross weight capacity Cone Stand (12 leg) 6500 CB
90401201	95" stands for P/N 833, 835 & 836 (3" clearance, 4 leg)
90401202	95" stands for P/N 833, 835, & 836 (12" clearance, 4 leg)
79500000	142" Cone Stand 100 ton gross weight capacity (12 leg)

CONE BOTTOM STANDS 45°	
Part No.	Description
78800000	64" Cone Stand 500-1000-1500 (4 leg)
79200000	90" Cone Stand 45 ton gross weight capacity (8 leg)
78801000	475 Gallon basket & stand for P/N H15603--



MIX TANK STANDS	
Part No.	Description
48400000	17 mix tank stand (18"Wx28"L) 24 lbs.
48600000	35-65-110 mix tank stand (30"Wx20"L) 29 lbs.



## POLY CONE BOTTOM TANKS & STANDS

The new polyethylene cone stands eliminate corrosion and the associated maintenance costs. The stands are forkliftable, and are designed not to interfere in viewing the liquid levels of the cone tank.



POLY CONE BOTTOM STANDS & CONE BOTTOM TANKS							
Description	Diameter	Height w/stand	Manway	Part No.	Outlet Specs	Stand	FOB
225 w/poly stand	48"	55"	18"	H15604--	O-2"	Included	C
325 w/poly stand	48"	66"	18"	H15605--	O-2"	Included	C
1000	86"	78"	10"	189--	O	1003 Poly or 79000 Steel	C
1400	86"	90"	10"	190--	O	1003 Poly or 79000 Steel	C
1775	86"	105"	10"	191--	O	1003 Poly or 79000 Steel	C
Poly Stand Only	86"	36"	N/A	1003--	N/A	--	C

[www.snydernet.com](http://www.snydernet.com)