



AG TANK CATALOG



AGRICULTURAL TANKS FOR STORAGE, TRANSPORT,
& APPLICATION

Vertical • Horizontal • Cone Bottom • Transport • Containment

www.snydernet.com

The Snyder Advantage

When you need tanks for your operation, what do you look for? Quality? Value? Selection? For over 50 years Snyder Industries has proudly offered all three. That's the Snyder Advantage. We build quality into every one of our strong, lightweight, rotationally molded polyethylene tanks. The seamless, single piece construction gives them long life and makes them a better value. And we offer tanks for every application, in sizes from 8 to 16,500 gallons.



VERTICAL TANKS

Snyder's vertical tanks are strong and versatile enough for your bulk storage needs. These tough, lightweight tanks come in a variety of styles and sizes from 65 gallons to 16,500 gallons. Snyder vertical tanks feature stable, flat bottoms, maximum drainage siphon assemblies and molded-in tie down lugs.

Pages 4-5



CONE BOTTOM TANKS

Snyder's mix tanks are available in sizes from 17 gallons to 110 gallons, while our cone bottom storage tanks hold from 475 gallons to 11,850 gallons. The 15°, 30° and 45° cone options provide fast discharge and complete drainage, and both our mix tanks and storage tanks feature engineered, welded steel stands. Optional fitting locations and gallonage tapes are also available.

Pages 6-7



POLY CONE STANDS

The new polyethylene cone stands eliminate corrosion and the associated maintenance costs. The stands are forkliftable, and are designed not to interfere in viewing the liquid levels of the cone tank.

Page 7



APPLICATOR TANKS

Snyder manufactures a wide line of applicator tanks in sizes from 8 gallons to more than 2,600 gallons and a variety of styles including lawn and garden, horizontal, elliptical, champion, side-mount and spherical. All tanks feature manways for easy filling, ultraviolet inhibitors to protect the tank and its contents, molded-in gallonage indicators and more.

Pages 8-9

www.snydernet.com



*If quality, value and selection are vital to your operation, give us a call.
It pays to give yourself the Snyder Advantage.*

CENTER SUMP DRAINABLE & ELLIPTICAL LEG TANKS

Perfect for nurse applications. Snyder leg tanks eliminate the need for steel mounting saddles and cradles and come in a variety of sizes. Snyder leg tanks feature screw-on and hinged leak-proof lids, recessed areas for tie downs, molded-in gallonage markers and sturdy self-supporting molded-in legs.



Total drain tanks feature total drain center sumps to ensure complete drainage. Total drain bolted fitting is a standard option, all angles in the tank drain to the center sump for complete product application. No wasted liquids equal valuable savings.

Page 10

LEG TANKS & SUPER NURSE TANKS

For nurse applications. Snyder Super Nurse and Elliptical Leg tanks eliminate the need for steel mounting saddles and cradles and come in a variety of sizes. These tanks feature screw-on and hinged leak-proof lids, recessed areas for tie downs, molded-in gallonage markers and sturdy self-supporting molded-in legs.



Pages 11

VALUE ADDED TANKS, UTILITY TANKS & CONTAINMENTS

The "Value Added" transport tanks are offered in two sizes, 2500 gallons and 3250 gallons. This heavy duty product allows direct mounting to a truck chassis and is supported by a heavy duty frame. The 3250 gallon model comes with dual compartments to allow the transport of separate materials. These models come with a total drain outlet system to ensure full drainage of product.



Page 12

STEEL ACCESSORIES & FITTINGS

To fully customize your Snyder tank to fit your farm's needs, Snyder offers a variety of fittings. Types of materials available include polyethylene (standard), Poly Pro, PVC, and Stainless Steel.



Pages 13-14

www.snydernet.com

VERTICAL TANKS

Snyder's vertical tanks are versatile enough to use for everything from bulk storage to portable nurse applications. These tough, lightweight tanks come in a variety of styles and sizes from 65 gallons to 16,500 gallons. Snyder vertical tanks feature stable flat bottoms, maximum drainage siphon assemblies and molded-in tie down lugs.

Gallons	Diameter	Height	Manway	Part No.	Outlet Specs	FOB
65	23 1/4"	46"	6"	155--	A	L
120	32"	39"	10"	H15402--	V	C
150	33 3/4"	60"	14"	5710--	U	L
200	39 3/4"	56"	14"	5720--	U	L
200	40"	48"	6"	154--	V	L
200	33"	67"	10"	802--	E	M
205	42"	43"	10"	H15404--	V	C
300	35"	80"	10"	163--	E	M
310	42"	60"	10"	H16302--	N1	C
360	48"	51"	10"	H16303--	N1	C
400	45"	64"	18"	174--	N2	L
550	64"	46"	18"	806--	N2	P,M
550	64"	47"	18"	182--	N2	L,C
550	48"	74"	18"	180--	N2	L,M,P,C
710	60"	68"	18"	H17002	N2	C
850	48"	118"	18"	181--	N2	L,M,P
1000	60"	89"	18"	H18301--	N2	C
1100	64"	91"	18"	183--	N2	L,M,P
1100	86"	57"	10"	171--	I	L,P,C
1100	86"	86"	57"	81200--	I	M
1500	86"	74"	10"	177--	I	L,P,C
1500	86"	74"	18"	81201--	I	M
1550	64"	125"	18"	184--	N2	L,M,P
1650	86"	80"	10"	178--	I	L,P
2000	96"	84"	18"	H50501--	N2	C
2000	90"	88"	18"	5050--	N2	L,P
2000	90"	88"	18"	813--	N2	M
2100	102"	72"	18"	10018--	N2	P
2500	90"	107"	18"	5090--	N2	L,P
2500	90"	107"	18"	81400--	N2	M
2600	96"	98"	18"	H50904--	N2	C

FEATURES:

- Heavy duty bolted fittings standard on 550 gallon and above to reduce threat of fitting loosening during use.
- Fitting compatible siphon tubes to allow bottom fill of tank.
- Molded-in tie downs for securing and lift lugs for easy movement.
- UV inhibitors molded in for longer tank life.

See next page for outlet specs table.



VERTICAL TANKS

VERTICAL						
Gallons	Diameter	Height	Manway	Part No.	Outlet Specs	FOB
3000	96"	112"	18"	H5130--	H	C
3000	90"	127"	18"	5130--	H	L,P
3000	90"	126"	18"	8160--	H	M
3000	102"	97"	18"	74100--	H	L,P,C
4000	102"	131"	18"	8190--	H	M
4100	102"	130"	18"	736--	H	P
4100	120"	100"	18"	820--	H	M
4300	120"	104"	18"	H7420--	H	C
4400	90"	183"	18"	5210--	H	L
4500	102"	143"	18"	7420--	H	L
4700	102"	159"	18"	H74202--	H	C
5000	102"	156"	18"	10020--	H	P
5000	120"	116"	18"	H70001--	H	C
5000	102"	161"	18"	8210--	H	M
5400	142 1/2"	91"	18"	H70002--	H	C
5600	142"	102"	18"	5250--	H	P
6000	102"	188"	18"	7430--	H	L,P,C
6000	120"	132"	18"	7000--	H	L,P
6300	120"	140"	18"	8220--	H	M
6500	120"	145"	18"	H7140--	H	C
6600	120"	153"	18"	H53001--	H	C
6900	120"	154"	18"	7140--	H	L,P
7600	144"	123"	18"	H53002--	H	C
7650	142"	123"	18"	5300--	H	L
7800	120"	176"	18"	10032--	H	C
7900	120"	176"	18"	7370--	H	L
8300	120"	185"	18"	H53003--	H	C
8900	120"	194"	18"	7400--	H	L
9800	120"	215"	18"	7450--	H	L
10500	142"	169"	18"	5330--	H	L,P
10000	142 1/2"	161"	18"	H53301--	H	C
11000	142 1/2"	177"	18"	10053--	H	C
12500	142"	199"	18"	5350--	U/W	L
15000	142"	235"	18"	5370--	U/W	L
16500	142"	259"	18"	5380--	U/W	L

FEATURES:

- Heavy duty bolted fittings standard on 550 gallon and above to reduce threat of fitting loosening during use.
- Fitting compatible siphon tubes to allow bottom fill of tank.
- Molded-in tie downs for securing and lift lugs for easy movement.
- UV inhibitors molded in for longer tank life.

OUTLET SPECS:

- A = 6" fill, one 3/4" outlet with anti-vortex.
 B = 8" fill, one 1 1/4" outlet.
 E = 10" fill, one 2" HD outlet with siphon tube.
 I = 10" fill, one 2" bolted with siphon tube.
 H = 18" manway, one 3" bolted fitting with siphon tube.
 N1 = 18" manway, one 2" HD outlet with siphon tube.
 N2 = 18" manway, one 2" bolted outlet with siphon tube.
 U = No holes or fittings.
 Fittings can be ordered separately.
 V = 6" screw-on cap, one 1 1/4" outlet fitting.
 W = 18" manway.



CONE BOTTOM TANKS

Snyder's mix tanks are available in sizes from 17 gallons to 110 gallons, while our cone bottom storage tanks hold from 475 gallons to 11,850 gallons. The 15°, 30° and 45° cone options provide fast discharge and complete drainage, and both our mix tanks and storage tanks feature engineered welded steel stands. Optional fitting locations and gallation tapes are also available.

CONE BOTTOM TANKS

Gallons	Diameter	Height w/stand	Manway	Part No.	Outlet Specs	Stand Required	FOB
30° Cone Bottom							
70	32"	50"	8"	H15601--	T		C
475	60"	69"	18"	H15603--	O	78801000	C
1000	86"	83"	10"	189--	O	79100000	L,C
1250	95"	84"	18"	8310--	O	90401202	M
1400	86"	93"	10"	190--	O	79100000	L,C
1600	95"	87"	18"	8330--	O	90401202	M
1775	86"	111"	10"	191--	O	79100000	L,C
2000	90"	125"	18"	5070--	O	79100000	L
2500	90"	148"	18"	5110--	O	79100000	L,C
2600	95"	125"	18"	8350--	O	90401201/1202	M
3000	90"	167"	18"	5150--	O	79100000	L,C
3000	95"	141"	18"	8360--	O	90401201/1202	M
5500	90"	255"	18"	7040--	O	79100000	L
6500	90"	296"	18"	7180--	O	79300000	L
6900	142"	160"	18"	5280--	O	79500000	L
8250	142"	184"	18"	5320--	O	79500000	L
11850	142"	239"	18"	5340--	O	79500000	L
45° Cone Bottom							
500	64"	81"	18"	6190--	O	78800000	L
1000	64"	120"	18"	5000--	O	78800000	L
1500	64"	158"	18"	5010--	O	78800000	L
2850	90"	163"	18"	5100--	O	79200000	L
4350	90"	217"	18"	5180--	O	79200000	L
15° Cone Bottom							
3000	90"	136"	18"	7460--	O	N/A	L

MIX TANKS

Gallons	Diameter	Height	Part No.	Outlet Specs	Stand Required	FOB
17	18 1/2"	34"	185--	K	48400000	L
35	31"	34"	158--	M	48600000	L
65	31"	41"	156--	M	48600000	L
110	31"	56"	607--	M	48600000	L

OUTLET LEGEND

K = 8" screw-on cap, 1 1/4" outlet with anti-vortex.

L = Removable top, one 3/4" outlet, one 1 1/2" or 2 1/2" molded-in hose barb (optional 3/4" to 1 1/4" fitting available).

M = 10" fill, one 3/4" outlet, one 1 1/2" or 2 1/2" molded-in hose barb (1 1/4" fitting available).



OUTLET LEGEND:

Q = 10" or 18" fill, and one 2" bolted outlet.
O = 18" manway, one 3" total drain bolted outlet.

Add 26" to the tank height to get overall height in stand.



FEATURES:

- Molded-in gallonage markers (indicators).
- Slope bottom for easy draining and accurate measurement.
- Standard 1 1/4" fitting.
- UV inhibitors are molded in for longer tank life.

www.snydernet.com



CONE BOTTOM TANKS W/POLY STANDS

STEEL CONE BOTTOM STANDS

CONE BOTTOM STANDS 30°

Part No.	Description
79000000	86" 1000-1450-1650 Cone Stand (4 leg)
79100000	90" 45 ton gross weight capacity Cone Stand (8 leg)
79300000	90" 45 ton gross weight capacity Cone Stand (12 leg) 6500 CB
90401201	95" stands for P/N 833, 835 & 836 (3" clearance, 4 leg)
90401202	95" stands for P/N 833, 835, & 836 (12" clearance, 4 leg)
79500000	142" Cone Stand 100 ton gross weight capacity (12 leg)

CONE BOTTOM STANDS 45°

Part No.	Description
78800000	64" Cone Stand 500-1000-1500 (4 leg)
79200000	90" Cone Stand 45 ton gross weight capacity (8 leg)
78801000	475 Gallon basket & stand for P/N H15603--



MIX TANK STANDS

Part No.	Description
48400000	17 mix tank stand (18"Wx28"L) 24 lbs.
48600000	35-65-110 mix tank stand (30"Wx20"L) 29 lbs.



POLY CONE BOTTOM TANKS & STANDS

The new polyethylene cone stands eliminate corrosion and the associated maintenance costs. The stands are forkliftable, and are designed not to interfere in viewing the liquid levels of the cone tank.



POLY CONE BOTTOM STANDS & CONE BOTTOM TANKS

Description	Diameter	Height w/stand	Manway	Part No.	Outlet Specs	Stand	FOB
225 w/poly stand	48"	55"	18"	H15604--	O-2"	Included	C
325 w/poly stand	48"	66"	18"	H15605--	O-2"	Included	C
1000	86"	78"	10"	189--	O	1003 Poly or 79000 Steel	C
1400	86"	90"	10"	190--	O	1003 Poly or 79000 Steel	C
1775	86"	105"	10"	191--	O	1003 Poly or 79000 Steel	C
Poly Stand Only	86"	36"	N/A	1003--	N/A	--	C

APPLICATOR TANKS



FEATURES:

- Molded-in gallonage markers (indicators).
- 6" threaded opening.
- Molded-in inserts for 12 volt pump mounting.
- UV inhibitors are molded in for longer tank life.



FEATURES:

- Molded-in gallonage markers (indicators).
- Flat spots on each end for easy agitation.
- Design requires no additional support or banding.
- UV inhibitors are molded in for longer life.



FEATURES:

- 10" threaded cap for easy filling.
- Molded-in gallonage markers (indicators).
- Center sumps and end flat spots.
- UV inhibitors are molded in for longer life.

OUTLET LEGEND:

A = 6" fill, one 3/4" outlet with anti-vortex.
 H = 18" manway, one 3" bolted outlet w/siphon.
 C = 10" fill, two 1 1/4" outlet (1 w/anti-vortex).
 U = No holes or fittings. Fittings can be ordered separately.

LAWN & GARDEN TANKS

Gallons	Diameter	Height	Length	Part No.	Outlet Specs	FOB
8	12"	14 3/4"	16"	102--	R	L,P,C
12	12"	18 3/4"	16"	104--	R	L,P,C
15	14"	13 1/4"	32"	110--	G	L,C
25	17 3/4"	16 1/4"	36"	114--	G	L,C

OUTLET LEGEND: G = 6" Cap, no outlet.
 R = 6" fill, one 1" diameter 3/4" long 1/2" ID threaded, molded spout with 4 1/4" x 20" molded-in anchor inserts.

PCO TANKS

Gallons	Diameter	Height	Length	Part No.	Outlet Specs	FOB
30 PCO	19"	22 1/2"	24 1/2"	1091--	U - 6" Lid	L,P,C
50 PCO	19 1/2"	22 1/2"	38"	1171--	U - 6" Lid	L,P,C
100 PCO	30"	31"	38"	1201--	U - 10" Lid	L,P,C
150 PCO	36"	29"	48"	1571---	U - 10" Lid	L,P,C
200 PCO	36"	39 1/2"	48 1/2"	1661--	U - 10" Lid	L,P,C
325 PCO	38"	36 3/4"	69"	1721--	U - 18" Lid	C

OUTLET LEGEND: U=No holes or fittings. Fittings can be ordered separately.

HORIZONTAL TANKS

Gallons	Tank Width	Height	Length	Part No.	Outlet Specs	FOB
Rectangular Tanks						
50	25 1/2	16	40 1/2	1006000C--	U	M
100	25 1/2	28 1/2	40 1/2	1006100C--	U	M
Horizontal Tanks						
Gallons	Diameter	Height	Length	Part No.	Outlet Specs	FOB
25	23"	26 3/4"	18 1/2"	103--	A	P
55	23"	26"	38 1/4"	105--	A	L,P,M,C
110	30"	34 1/4"	49 3/4"	111--	C	L,P,M,C
150	30"	34 3/4"	60"	113--	C	M
150	32"	36 1/2"	55 1/4"	115--	C	L,C
200	32"	36 1/2"	70 1/2"	123--	C	L,M,C
200	38"	41 3/4"	52"	125--	C	M,C
300	38"	42"	71 1/2"	133--	C	P,M,C
400	42"	46 1/4"	72"	135--	C	L
500	42"	47"	92"	10029--	C	C
500	48"	52 1/4"	74 3/4"	139--	C	L,C
1000	64"	68"	86 1/2"	1431--	U - 10" Lid	L
2600	70"	70"	165"	H14301--	H	C



APPLICATOR TANKS

ELLIPTICAL TANKS

Gallons	Diameter	Height	Length	Part No.	Outlet Specs	FOB
300	48"	30"	72"	1471--	U - 10" Lid	C
400	48"	39"	72"	1241--	U - 10" Lid	C
525	58"	36"	81"	1481--	U - 10" Lid	L,C
850	68"	44"	93"	1501--	U - 10" Lid	L
1025	78"	47"	93 1/2"	1491--	U - 10" Lid	L
1300	86"	66"	89"	1001--	Q - 18" Lid	L

OUTLET LEGEND: U = No holes or fittings. Fittings can be ordered separately.



FEATURES:

- Molded-in gallonage markers (indicators).
- Low profile for ease of transport.
- Bottom sumps and recessed end flat spots.
- UV inhibitors are molded in for longer life.

CHAMPION SPRAYER TANKS

Gallons	Diameter	Height	Length	Part No.	Outlet Specs	FOB
300	46"	33"	64 1/2"	134--	C	L
500	57"	38 1/2"	77"	138--	C	L

OUTLET LEGEND: C = 10" FILL, TWO 1 1/4" Outlets, one with anti-vortex.



FEATURES:

- Molded-in gallonage markers (indicators).
- Unique design excellent for custom applications.
- Bottom sumps for ease of draining.
- UV inhibitors are molded in for longer life.

SIDEMOUNT/TRIM-VUE TANKS

Gallons	Diameter	Height	Length	Part No.	Outlet Specs	FOB
200 TV	32"	42 1/2"	48"	127--	C	L
200 STV	24"	45 1/2"	59"	126--	C	C
250 STV	24"	59"	59 3/4"	118--	C	C
260 TV	31"	48"	54"	131--	C	L

OUTLET LEGEND: C = 10" FILL, TWO 1 1/4" Outlets, one with anti-vortex.



FEATURES:

- Molded-in gallonage markers (indicators).
- Designed for easy viewing from tractor cab.
- Bottom sumps for better drainage.
- UV inhibitors are molded in for longer life.

SPHERICAL TANKS

Gallons	Diameter	Height	Part No.	Outlet Specs	FOB
1100	79"	79"	62602--	C	C

OUTLET LEGEND: L = 10" (Lnk) or 18" (CA) lid.



FEATURES:

- Designed for special applications, reduces sloshing.
- Bottom sump for better drainage.
- UV inhibitors are molded in for longer life.

CENTER SUMP DRAINABLE & ELLIPTICAL LEG

These tanks feature total drain center sumps to ensure complete drainage. Total drain bolted fitting is a standard option, all angles in the tank drain to the center sump for complete product application. No wasted liquids equal valuable savings.



FEATURES:

- Molded-in gallonage markers (indicators).
- Molded-in baffles to reduce sloshing.
- Total drain bolted fitting standard for complete drainage.
- 18" manway for easy access.
- UV inhibitors are molded in for longer tank life.

TOTAL DRAIN/SLOPE BOTTOM TANKS							
Gallons	Diameter	Height	Length	Part No.	Outlet Specs	Bands/Hoops Required	FOB
715 Slope	47"	49"	104"	10043--	T	N/A	L,M
1000 Slope	46"	48"	154"	541--	T	45900003	L
1250 Slope	46"	57"	154"	543--	T	45200007	L
1615 Slope	69"	61 1/4"	140"	10034--	T	45800009	M
2015 Slope	69"	72 1/4"	140"	10035--	T	45800011	M
3100 Slope	92"	74"	142"	75002--	T	45800000	L

OUTLET LEGEND

A = 6" fill, one 3/4" outlet with anti-vortex.

E = 10" fill, one 2" HD outlet with siphon tube.

H = 18" manway, one 3" bolted outlet.

Q = 18" manway, one 2" bolted fitting.

D = 18" manway, one 2" bolted outlet with siphon tube.

G = 6" cap, no outlet.

O = 18" manway, one 3" bolted total drain fitting.

S = 10" fill, one 1 1/4" outlet.

T = 18" fill, one 2" total drain bolted outlet.

ELLIPTICAL LEG TANKS							
Gallons	Diameter	Height	Length	Part No.	Outlet Specs	Hoops Required	FOB
1650	71"	55"	140"	1007--	H - 18" Lid	45800003	C,M
2000	84"	55"	142"	10023--	H - 18" Lid	45800007	P,C
2600	82"	70"	155"	8470--	H - 24" Lid	99402226	L,P,M,C
3000	92"	76"	142"	7500--	H - 18" Lid	45800000	L,P,M,C

OUTLET LEGEND: H = 18" Manway, one 3" bolted outlet with siphon tube.



FEATURES:

- Molded-in gallonage markers (indicators).
- Low profile for ease of transport.
- Molded-in baffles reduces sloshing.
- UV inhibitors are molded in for longer life.



www.snydernet.com

LEG TANKS & SUPER NURSE TANKS

Perfect for nurse applications, Snyder leg tanks eliminate the need for steel mounting saddles and cradles and come in a variety of sizes. Snyder leg tanks feature screw-on and hinged leak-proof lids, recessed areas for tie downs, molded-in gallonage markers and sturdy self-supporting molded-in legs.



FEATURES:

- Molded-in gallonage markers (indicators).
- Free standing HLT requires no cradles for support (optional).
- Ribbed for strength with built-in supports.
- UV inhibitors are molded in for longer tank life.

LEG TANKS

Gallons	Diameter	Height	Length	Part No.	Outlet Specs	Bands/Hoops Required	FOB
30	23"	25 3/4"	19 1/2"	108--	G	33900093	L,P,M,C
60	23"	25 3/4"	38"	106--	A	33900093	L,P,M,C
125	30"	34 1/2"	50"	112--	S	33900094	L,P,C
200	41"	31 3/4"	54"	122--	S	33900094	L
230	38"	42 1/2"	52"	128--	S	33900095	L,P,C
300	38"	42 1/2"	72"	132--	S	33900095	L,P,M
300	38"	38"	67"	H13201--	S	45400006	C
500	49"	49"	72"	H14001--	E	45300007	C
525	48"	52 1/2"	75"	140--	E	33900096	L,P,M
730	57 1/2"	57 1/2"	80"	136--	E	33900097	L,C,P



FEATURES:

- Molded-in gallonage markers (indicators).
- Molded-in baffles to reduce sloshing.
- Bolted fitting standard to reduce fitting loosening during use.
- UV inhibitors molded in for longer tank life.

SUPER NURSE TANKS

Gallons	Diameter	Height	Length	Part No.	Outlet Specs	Bands/Hoops Required	FOB
750	46"	48 1/2"	116 1/2"	130--	D	45900006	L
1025	48"	50"	139"	144--	D	45300003	L,P,C
1200	68"	40"	140"	832--	H	99402212	M
1600	68"	50"	140"	837--	H	99402217	M
1685	60"	62"	159"	146--	H	45500001	L,M
2000	60"	70 1/2"	160"	751--	H	45500002	L
3400	82"	86"	155"	7520--	H	45700001	L

OUTLET LEGEND

A = 6" fill, one 3/4" outlet with anti-vortex.

E = 10" fill, one 2" HD outlet with siphon tube.

H = 18" manway, one 3" bolted outlet.

Q = 18" manway, one 2" bolted fitting.

D = 18" manway, one 2" bolted outlet with siphon tube.

G = 6" cap, no outlet.

O = 18" manway, one 3" bolted total drain fitting.

S = 10" fill, one 1 1/4" outlet.

T = 18" fill, one 2" total drain bolted outlet.

www.snydernet.com



VALUE ADDED TANKS, UTILITY TANKS & CONTAINMENTS

VALUE ADDED SUPER NURSE ASSEMBLY						
Gallons	Diameter	Height	Length	Part No.	Bands/Hoops Required	FOB
2500HS	82"	72"	156"	846071327	Included	L,M
3250 Dual	92"	72"	178"	870071347	Included	L,M
VALUE ADDED SUPER NURSE - TANKS ONLY						
2500HS	82"	72"	156"	8460000C95003	N/A	L,M
3200HS Dual-right	92"	72"	178"	8240000C95002	N/A	L,M
3200 Dual-left	92"	72"	178"	8230000C95002	N/A	L,M

Tank assemblies have 24" transport lids, and 3" sumo outlets. 3250 Dual, has 2-24" transport lids, and 2-3" Sumos.
 Tank only, have 1-24" transport lid, and 1-3" sumo.



FEATURES:

- Molded-in gallonage markers (indicators).
- Heavy duty steel support.
- Snyder Unitized Molded Outlet (SUMO®) for complete drainage.
- UV inhibitors are molded in for longer life.

UTILITY TANKS					
Gallons	Diameter	Height	Part No.	Outlet Specs	FOB
150	54 1/2"	25 3/4"	160--	E	P
300	64"	32 1/2"	162--	E	P
450	64"	48"	165--	E	P

E = 10" fill, one 2" HD outlet with siphon tube



FEATURES:

- Molded-in gallonage markers (indicators).
- 300 and 450 gallon tanks have offset lid for easy-access side filling.
- Natural color is FDA compliant for water.
- UV inhibitors are molded in for longer tank life.

OPEN TOP TANKS				
Description	Diameter	Height	Part No.	FOB
650 Gallon	60"	60"	H13702--	C
1350 Gallon	72"	76"	H50301--	C
1550 Gallon	96"	52"	H50305--	C
2600 Gallon	120"	64 1/2"	H50306--	C
7100 Gallon	142 1/2"	103"	H52302--	C



FEATURES:

Cylindrical open top tanks can be utilized as primary process or mix tanks or for secondary containment of an inner tank.

STEEL ACCESSORIES

SADDLES

Part No.	Description	Width	Length	Weight
40100000	25x23"	16"	18"	17 lbs
40400000	110x30", 150x30"			
	150x32", 200x32"	12"	21"	38 lbs
40500000	200x38", 300x38"	12"	28 1/2"	57 lbs
40800000	400x42"	12"	30 1/2"	69 lbs
40900000	500x48"	12"	37 1/2"	78 lbs

Two curved support sections with bands and padding for one tank. 25x23" requires only 1 curved support section.

CRADLES

Part No.	Description	Width	Length	Weight
43100000	110x30", 150x32"	24"	40"	55 lbs
43200000	150x30", 200x32"	24"	55"	67 lbs
43600000	200x38"	36"	40"	70 lbs
43700000	300x38", 400x42"	36"	55"	86 lbs
44000000	500x48"	45"	55"	106 lbs

PADDING & BANDS

Part No.	Description
33200003	Padding-12"x36 1/2"
33900035	47" band each (fits 25x23", 55x23")
33900037	71 1/2" band each (fits 110x30", 150x30", 150x32", 200x32")
33900038	80" band each (fits 200TV, 260TV, 200 champ, 525 elliptical)
33900039	84" band each (fits 200x38", 300x38")
33900040	102" band each (fits 500x48", 720x54")
33900041	129" band each (fits 1000x65")
33900093	56" leg tank band each (fits 30 & 60 gallon)
33900094	74" leg tank band each (fits 125 gallon)
33900095	95" leg tank band each (fits 230 & 300 gallon)
33900096	119" leg tank band each (fits 500 gallon)
33900097	136" leg tank band each (fits 730 gallon)

Elliptical Bands

33900104	64" band (fits 300 elliptical)
33900105	100" band (fits 850 elliptical)
33900106	111" band (fits 1000 elliptical)
34700014	J-bolt Package Horizontal Leg Tanks

SKID ASSEMBLIES

Part No.	Description	Width	Length	Weight
45100000	200 x 38"	28"	41"	110 lbs
45400000	500 x 48"	38"	48"	164 lbs
45600000	1000 x 65"			
45200001	1000 X 46"			

HOOP ASSEMBLIES

Part No.	Description
45400006	300 X 38" hoop assembly (2)
45300007*	500 X 49" hoop assembly (2)
45300001	525 x 48" hoop assembly (2)
45400002	730 x 54" hoop assembly (each)
45200003**	750 x 46" hoop assembly (3)
45900004	1000 x 46" center drain hoop assembly (4)
45300003	1025 x 48" hoop assembly (4)
45800009	1615 drainable hoop assembly
45500001	1685 x 60" hoop assembly (4)
45500002	2000 x 60" hoop assembly (4)
45800011	2015 drainable hoop assembly
45700001	3400 super nurse assembly (4)
34700529	J-bolt package for 1025-2000 super nurse

Elliptical Hoop Assemblies

99402212	1200 Elliptical hoop assembly
99402217	1600 elliptical hoop assembly
45800003	1650 elliptical hoop assembly (4)
45800007	2000 elliptical hoop assembly
99402226	2600 super nurse hoop assembly (4)
45700004	2600 elliptical hoop assembly (4) (narrow)
45800000	3000 elliptical hoop assembly (4)
34700530	J-bolt package for 3000 elliptical
34701580	J-bolt package for 2600 elliptical (3/4")

LADDERS

90404227	Ladder - 2600 SN (P/N 847--)
----------	------------------------------



Saddles, pads and bands



Cradles



Skid assemblies



Hoop assemblies

FITTINGS & ACCESSORIES

DOUBLE THREADED APPLICATOR FITTINGS

Part No.	Description
34300005	3/4" SII std. poly
34300006	1" SII std. poly
34300003	1 1/4" SII std. poly
34300008	1 1/2" SII std. poly

All fittings include EPDM gaskets.



DOUBLE THREADED FITTINGS

Part No.	Description
34100104	2" double threaded w/ EPDM
34701142	2" double threaded w/ VITON
34700840	2" double threaded w/ EPDM (SST)
34700845	2" double threaded w/ EPDM (LST)
34700847	2" double threaded w/ VITON (SST)
34700848	2" double threaded w/ VITON (LST)
34300120	3" double threaded w/ EPDM
34700542	3" double threaded w/ VITON
34700539	3" double threaded w/ EPDM (SST)
34700538	3" double threaded w/ EPDM (LST)
34700546	3" double threaded w/ VITON (SST)
34700545	3" double threaded w/ VITON (LST)

SST = short siphon tube
LST = long siphon tube



BOLTED DOUBLE FLANGE FITTINGS

Part No.	Description
34100103	2" poly pro bltd w/EPDM
34701111	2" poly pro bltd w/VITON
34700842	2" poly pro bltd w/EPDM (SST)
34700841	2" poly pro bltd w/EPDM (LST)
34700852	2" poly pro bltd w/VITON (SST)
34700849	2" poly pro bltd w/VITON (LST)
34100105	3" poly pro bltd w/EPDM
34701112	3" poly pro bltd w/VITON
34700844	3" poly pro bltd w/EPDM (SST)
34700843	3" poly pro bltd w/EPDM (LST)
34700851	3" poly pro bltd w/VITON (SST)
34700850	3" poly pro bltd w/VITON (LST)

SST = short siphon tube
LST = long siphon tube



REPLACEMENT GASKETS for POLY PRO BOLTED FITTINGS

Part No.	Description
33100186	EPDM gasket for 2" PP bltd
33100187	VITON gasket for 2" PP bltd
33100188	EPDM gasket for 3" PP bltd
33100189	VITON gasket for 3" PP bltd



LIDS & MANWAYS

Part No.	Description
34700088	10" threaded cap
34300038	5" McPhee cap
34300047	6" screw-on cap
34300216	8" lid assembly
34701243	14" lid assembly
34300012	18" lid assembly
34300226	4" insert w/vent for 18" lid
34100125	18" hinged lid assembly
34700352	24" lid assembly
8570000C95401	24" poly hinged lid (new)
34500008	Poly lid tie



STAINLESS STEEL BOLTED FITTINGS

34701596	2" bltd FXF SS316-3/EPDM
34701597	2" bltd FXF SS316-3/VITON
34701598	3" bltd FXF SS316-3/EPDM
34701599	3" bltd FXF SS316-3/VITON
34701600	4" bltd FXF SS316-3/EPDM
34701601	4" bltd FXF SS316-3/VITON



REPLACEMENT GASKETS for DOUBLE THREADED FITTINGS

Part No.	Description
33100001	EPDM for applicator ftg.
33100002	VITON for applicator ftg.
33100140	EPDM gasket for 2" PE ftg.
33100139	VITON gasket for 2" PE ftg.
33100142	EPDM for 3" PE ftg.
33100006	VITON for 3" PE ftg.



REPLACEMENT SIPHON TUBES

34100148	2" Poly Pro long siphon tube
34700534	2" Poly Pro short siphon tube
34100149	3" Poly Pro long siphon tube
34700535	3" Poly Pro short siphon tube



ANTI-VORTEX VENTS

Part No.	Description
34700007	anti-vortex (1-1 1/4" ftg.)
34300009	anti-vortex (cap only)
34100115	2" (vent cap)
34100114	2" (vent cap with mesh screen)

STRESS RELIEVER

Part No.	Description
34100380	2" Stress Reliever - adapter only.
34701647	2" Bolted Fitting with Stress Reliever adapter & siphone tube.
34701630	3" Bolted fitting with Stress Reliever adapter & siphon tube.
34100379	3" Stress Reliever - adapter only.



BOLTED TOTAL DRAIN FITTINGS

Part No.	Description
34100116	2" PP Total Drain bltd/EPDM
34100117	3" PP Total Drain bltd/EPDM

Exclusively for cone bottom and center sump tanks.



GALLONS PER VERTICAL INCH

Gallons Per Vertical Inch

Use as Nominal Measurements

Numbers listed are for 1.5 specific gravity tanks –on tanks less than 1.5 S.G., numbers could be a little more, tanks with a higher S.G., numbers could be a little less.

<u>Tank Diameter</u>	<u>Gallons per Vertical Inch</u>
64" Diameter Tank	13.7
86" Diameter Tank	24.8
90" Diameter Tank	27.24
102" Diameter Tank	34.68
120" Diameter Tank	48.14
142" Diameter Tank	67.8

Gallon Capacity of Cone Section in Cone Bottom Tanks

30° Cone Bottoms – Lincoln, Philippi

<u>Diameter</u>	<u>Gallons</u>
86"	203.61
90"	231
142"	986.1

30° Cone Bottoms – Marked Tree

95"	275
-----	-----

45° Cone Bottoms – Lincoln

64"	143.15
90"	411.42

Warranty

Snyder Industries provides a three (3) year warranty from date of shipment on all tanks. Remedy of the buyer is limited to the replacement of any defective product (or its component, where applicable), FOB point of manufacture. The buyer's remedy under this warranty does not include replacement of any material lost through leakage or damages for injury to persons or property caused by such leakage.

Contact your Snyder representative for assistance if a warranty situation should occur.

5 YEAR WARRANTY

Five (5) year warranty available on specific heavy duty tanks

CHEMICAL COMPATIBILITY

Always check your chemical compatibility with tanks, fittings, and gaskets. Contact your chemical supplier or your Snyder customer service representative for assistance.

www.snydernet.com



Our Mission

Our mission at Snyder Industries is to provide our customers with liquid bulk handling container solutions that exceed their safety and performance requirements at the lowest possible cost.



Authorized Distributor:



P.O. Box 4583 • Lincoln, Nebraska • 68504 • 402-467-5221 • Fax: 402-465-1220 •
sales@snydernet.com

*Other manufacturing Locations: Marked Tree, Arkansas • Philippi, West Virginia •
Chowchilla, California • Mancelona, Michigan*

www.snydernet.com